♦ DCBI - 100 Online Visual Bottle Inspection Machine

TECHNICAL SPECIFICATION

Model No	DVBI - 100	
DIRECTION OF MOVEMENT	Left to Right	
OUTPUT*	Up to 100 Containers/minute	
NUMBER OF OPERATOR	Four (2X2, Two Side Deated)	
POWER CHARACTERISTICS	0.5 HP / 220 Volts / 50 Hz.	
HEIGHT OF CONVEYOR*	850 mm To 910 mm	
MACHINE DIMENSIONS**	1830 mm (L) X 850 mm (W) 1525 mm (H)	

Note: we reserve the right to change Specification without prior notice.

Denmark

SALIENT FEATURES

- Direct gear drive.
- Length can be made as per customer requirement.
- PVC black & white board as per GMP norms.
- UHMW self lubrication guide below chain.

- · Ss elegantly matt finishing.
- Adjustable height of conveyor belt, to align with other machine of the line
- Self-alignment bearing for easy maintenance.

♦ DPCB - Packing Conveyor Belt



NPUT & TECHNICAL SPECIFICATION

Model No	DPCB		
DIRECTION OF MOVEMENT	Left to right		
POWER CHARACTERISTICS	0.5 HP / 440V / 50 Hz.		
CONVEYOR HEIGHT	850 mm to 910 mm		
BELT WIDTH	9" or 12" as per requitement		
BELT DETAILS	PVC, endless 2 ply sandwich, 2 mm thickness		
MACHINE DIMENSIONS	9" WIDTH BELT	As per requirement (L) X 830 mm (W) 850 mm (H)	
	12" WIDTH BELT	As per requirement (L) X 900 mm (W) 850 mm (H)	
CONTAINER SIZE	@ 22 mm to @ 100 mm Diameter		
MACHINE POWER SUPPLY	1 / 3 Phase + Neutral + Earthing		

Note: we reserve the right to change Specification without prior notice.

SALIENT FEATURES

- Structure is made of S.S. 304, 30 mm sq. pipe, 16 SWG with matt finish.
- Belt-alignment system for long life 7 straight running of belt.
- Direct gear drive.

- Length can be made as per customer requirement.
- S.S elegantly matt finishing.
- Adjustable height of conveyor belt, to align whit other machine of the line.